

# PARATHOM CLASSIC B 40 270° ADV 6 W/827 E14 N/A

PARATHOM advanced CLASSIC B | Dimmable LED lamps, classic mini-candle shape



#### Areas of application

- Domestic applications
- General illumination
- Chandeliers
- Outdoor applications only in suitable luminaires

#### Product benefits

- Very long lifetime of up to 25,000 h
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

#### Product features

- LED alternative to conventional lamps
- Good quality of light; color rendering index  $R_a: \ge 80$ ; constant chromaticity
- High color consistency:  $\leq$  6 SDCM
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps



#### Technical data

## **Electrical data**

Rated wattage	6.00 W
Nominal wattage	6.00 W
Nominal voltage	220240 V
Operating frequency	5060 Hz
Power factor $\lambda$	0.50
Claimed equiv. conventional lamp power	40 W


## Photometrical data

Nominal luminous flux	470 lm	
Rated luminous flux	470 lm	
Color temperature	2700 К	
Color rendering index Ra	≥80	
Light color (designation)	Warm White	
Standard deviation of color matching	≤6 sdcm	

## Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	0.0 s

## **Dimensions & weight**



Overall length	106.0 mm
Diameter	35.0 mm
Outer bulb	B35
Length	106.0 mm

#### Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen main.fact.at end of nom.life time	0.70
Lumen maintenance at end of service life	0.70

#### Additional product data

Base (standard designation)	E14	
Mercury content	0.0 mg	
Mercury-free	Yes	
Design / version	Frosted	
Appropriate disposal acc. to WEEE	Yes	
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In preparation	

### Capabilities

Dimmable	Yes
----------	-----

#### Certificates & standards

Energy efficiency class	A+	
Energy consumption	6 kWh/1000h	

#### Country specific categorizations

ILCOS	DRBB/F-6-220-240-E14-35	
Order reference	PCLB40DIM 6W/82	

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899961784	PARATHOM CLASSIC B 40 270° ADV 6 W/827 E14 N/A	Shipping carton box 10	205 mm x 87 mm x 123 mm	2.19 dm³	778.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For dimming conformity see

www.ledvance.com/dim

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.